

Vehicle-No.: 506006



Mercedes-Benz 4163 LS ACTROS 8X4/4 heavy load tractor

AVG Trucks GmbH

Gwinnerstraße 36 60388 Frankfurt/M

Telefone: +49 (0) 69-942138-0 Fax: +49 (0) 69-942138-38

info@avg-trucks.de http://www.avg-trucks.de

Euro 96.500,00	+ Mwst.
----------------	---------

First registration	04.06.2018
Mileage	234.400 km
Emission level	6
Engine power	460/626 kW/PS
Total weight	41.000 kg
Kerb weight	13.575 kg
Payload	27.425 kg
Wheelbase	3.900 mm
Height of edge of trailer tray	1.420 mm
Suspension	parabolic/air
Operator's cab	GigaSpace

Equipment

1AV Trailing front-axle steared

A1E Front axle 9,0 t

A2G Rear axle, crown wheel 300, planets, 13.4 t

A6A Final drive ratio i = 4.571

B1B Electronic braking system with ABS and ASR

B2A Disk-brakes front- and rearaxle

B2Z Parking brake, additionally on the front axle

C1Z Wheelbase 3.900 mm

C6Q Anti roll bar front

D0A leather Steering Wheel

DOC Interior concept style line

D0U Smoke detector, in the driver's cab

D1C Driver's suspension seat comfort

D1P Passenger suspension seat, comfort

D3A Comfort Bed, top, width, height-adjustable

D3B Comfortable bed, below

D3M Mattress, Premium Comfort, below

D3N Top mattress, Premium Comfort

D4T Curtain across bed

D4X 2-piece electric sunblind, windscreen

D4Z Sun blind side, driver and passenger side

D5B Ambient lighting

D6C Electric parking air conditioner

D6G automatic climate control

D6I Residual heat

D6M Hot water heater, cab

D7A Thermal insulation in addition

D7J Drawers under bed

D7N Flexible shelving system for filing through front window

D7V Table on the passenger side

D8M Sliding / tilt sunroof electric, glass version

ESR Power Socket 24 V 25 A, from passenger frontwell ESR Socket 24 V 15 A, side with larger light ESW Traction, speed tims 30 km / h ESW Tractions contributed with hazard tights ETF Cable tenude control for air suspension ESB Maio socket ESW Tractions of electrical devices FOT Marcades start it FOT Marcades start it FOT displays cab 2.30 m vide, flat froor FIR Cab long FSP Cab hough? 750 mm top FSP Cab FSP C	
EAW Traction, speed inmit 20 km / h EVP Revening alarms combined with hazard lights EVP Cable remote control for air suspension E86 Nato socket E86 Preparation for destricial devices FOT Mercodes star lit F11 GigaSpace cab 2:30 m wide, flat floor F1R Cab long F2H Cab with 2:50 m F2H Ca	E3R Power Socket 24 V / 25 A, front passenger footwell
EVP Routing palarms control for air suspension EVP Cable remote control for air suspension ESD Nate sockets ESD Perpantation for electrical devices FOT Mercades star it FU GigsSpace: cab 2:30 m wide, flat floor FUR Cab long EVP Cab wide 756 mm top EVP Cab, height 756 mm top EVP Cab, height 756 mm top F3V Cab subrago comportment used fail pielt F4X Storage compartment used fail pielt F4X Storage compartment used fail pielt F4X EVP S	E3S Socket 24 V / 15 A. side wall shelf right
### ### ### ### ### ### ### ### ### ##	E4W Traction, speed limit 30 km / h
EBR Nationation for electrical devices FOT Memoration for electrical devices FOT Memorates star in FUL Glass/Space on br. 2:0 m wide, flat floor FUR Clab width 2.60 m F2P Clab width 7.65 mm top F2P Clab width 7.65 mm top F2P Clab width 7.65 mm top F3V Clab using on comfort with air suspension, F3V Clab using on comfort with air suspension, F3V Storage compartment outside flap let F4V Storage compartment outset flap, right F4Z F3D. Sun visor, exterior, transparent F3D. Sun visor, exterior, transparent F3D. Sun visor, exterior, transparent F3R F3D. F3D	E6Y Reversing alarms combined with hazard lights
EBG Preparation for electrical devices FOT Mercedes star in FOT CligispSpace abb 230 mivide, flat floor FIR Cab long FEP Cab, height 765 mm top FEP Cab, height 765 m	E7F Cable remote control for air suspension
FOT Mercades star lit F14 GispSpace cab 2.30 m wide, flat floor F15 Cab long F26 Cab, width 2.50 m F27 Cab, lenjeth 765 mm top F29 Cab, height 765 mm top F29 Cab, height 765 mm top F37 Cab luling decrobydraulic F37 Storage compartment outself lap left F47 Storage compartment outself lap left F47 Storage compartment outself lap left F47 Storage compartment outself lap left F48 Storage compartment outself lap left F48 Storage compartment outself lap left F49 Storage compartment outself lap left F48 Storage compartment outself lap left F48 Lab mixtor, exterior, transparent F58 Air horns, cab roof F58 Canfort Lock F58 Kain / light sensor G58 Mercedes PowerShift 3 H16 Divers's seat heating H16 Divers's seat heating H16 Divers's seat heating H16 Divers's seat heating H17 Wheel formula 8844 I68 Air suspension, rear axie J28 Auxiliandia radio touch J28 Avxiliandia radio touch J39 Pre-installation for toll collection J39 Pre-paralton for Truck Data Center 6 (DTCO) KX59 Ax880c and KX0 Bitris KX6 900-liter tank L14 Bit Xaroon headilights L15 L15 L16 Jallights L34 Spotialight vashers M37 Morco CMM73, R6, 15.61, 460 kW (£25 hp) 3000 Nm M58 Engine version Euro 6, with OBB-C M57 Turnbocompound M57 High Performance Engine Brake M58 Turnbocompound M57 High Performance Engine Brake M57 Turnbocompound M57 High Performance Engine Brake M58 Turnbocompound M57 High Harden R60 Mm M57 High Wheel height, H = 190 mm M58 Land Revening assistant S11 Alarmase assistant S11 Alarmase assistant S11 Alarmase Assistant S12 Alarmase Assistant S13 Acria Countries S25 Cruise control	E86 Nato socket
F1R CispaSpace cab 2.30 m wide, fist floor F1R Cab long F2P Cab, height 756 mm top F3C Cab suspension comfort with air suspension, F3Y Storage compartment outside flap left F4X Storage compart	E9G Preparation for electrical devices
F1R Cab long F2P Cab, helpit 766 mm top F2P Cab, helpit 766 mm top F3C Cab suspension comfort with air suspension, F3Y Cab litting electrohydraulic F4X Storage compartment outside flap left F4Y Storage compartment outside flap left F4Y Storage compartment outside flap left F4X	F0T Mercedes star lit
F2P Cab width 2.50 m F2P Cab height 765 mm top F3P Cab height 765 mm top F3P Cab billing electrohydraulic F4X Storage compartment outside flap left F4X Stor	F1J GigaSpace cab 2.30 m wide, flat floor
F2P Cab, height 765 mm top F3C Cab inseperation comfort with air suspension, F3C Cab intine gleechroylgraulie F3C Storage compartment outside flap left F3C	F1R Cab long
F3C Cab suspension comfort with air suspension, F3Y Cab tilling electrohystraulic F4X Storage compartment outsel flap left F4Y Storage compartment outsel flap, right F4Z ISD F5C ISUN visor, exterior, transparent F5R Air horns, cab mod F5E Lobding system with central locking F5E Confort Lock F5C F3C ISD visor, exterior, transparent F5C Air horns, cab mod F5C Tomfort Lock F5C R3M rilight sensor G3Y Turbor elearder dutch G3Y Turbor elearder dutch G3Y Turbor elearder dutch G3Y Turbor elearder dutch G3Y H16D visors seat heating H4L Wheel formula 8x4/4 H5D Xir suspension, rear axide J3H Millimedia radio touch J3K Speaker, 2-way system J3Z Axle load measuring device J3Z Maxxin, a side wall shelf, right J3Z Axle load measuring device J3D P1e-installation for toil collection J3N Preparation for Truck Data Center 6 (DTCO) K3V ASTILle tank 60 liters K5S 900-liter tank L1A Bi-Xenon headlights L1A Bi-Xenon headlights L1N F5Q lights, LED-Daytime running lights, cornering lights L1A Specifight, below L3Z Headlight washers M3Y Motor OMAY3, R5, 15, 61, 460 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N7 Motor OMAY3, R6, 15, 61, 460 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N7 Motor Output back, b, lange 100 mm, 650 Nm OYX Sight Peakee Q1Z Front spring 10.5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm R1.3 ALU light tental rims S1L Alcrees assistant S1L Alcrees assistant S1L Alcrees assistant S1L Alcrees assistant	F2H Cab width 2.50 m
F3Y Cab tilling electrohydraulic F4X Storage compartment outside flap left F4X Storage compartment outside flap left F4X Storage compartment outside flap, right F4Z ISb F5L Sun visor, exterior, transparent F6E Air horns, cab zor of F6E Locking system with central locking F6E conflort Lock F3K Rain / Light sensor G3Y Turbo retarder clutch G3G Marcadeas Power-Philt 3 H16 Drivers seat heating H17 Drivers seat heating H18	F2P Cab, height 765 mm top
F4X Storage compartment outside flap left F4X Storage compartment outer flap, right F4X Storage compartment outer flap, right F4X Storage compartment outer flap, right F5R Lish rivsr, eab roof F5R Canning system with earntal locking F6R comfort Lock F5X Rain / light sensor G5X Turbor ratarder cutch G5G Mercedes PowerShift 3 H16 Dinver's seat heating H16 Wheel Command 8x44 H16 Xir suspension, rear axis J2H Multimedia radio touch J2K Speaker, 2-vay system J2M Aux-in, a side wall shelf, right J3Z / xic load measuring device J3D Pre-installation for toil collection J3N Pre-paration for Truck Data Center 6 (DTCO) K3V AdBlue bank 60 liters K56 900-liter tank L1A Bi-Xeron headlights L1N Fog lights, LED-Daytmer running lights, cornering lights L1N Fog lights, LED-Daytmer running lights, cornering lights L3A Spotlight, below L3A Spotlight, below L3A Fendadight washers M3V Motor OMAT3, R6, 15.6 I. 480 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N5Z Transmission oil cooling N7I Motor output back, b, lange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10.5 I. 3-leaf Q4L Efft wheel height, H = 190 mm L3A AU light metal rims S1H Lane keeping assistant S1L Alcruess assistant S1L Alcruess assistant S5L Actives bentzed	F3C Cab suspension comfort with air suspension,
F4Y Storage compartment outer flap, right F4Z IfSD IS JAM visor, exterior, transparent F6R Air homs, cab roof F8E Locking system with central locking F8E comfort Lock F8C Rain / light sensor G3Y Tubo restarder clutch G5G Marcedes PowerShift 3 H16 Driver's seat heating HL Wheel formula 8x44 KAYA IS AS IN AIR SHAN SHAN SHAN SHAN SHAN SHAN SHAN SHAN	F3Y Cab tilting electrohydraulic
F42 f5b F5L Sun visor, exterior, transparent F5R Ar home, cab ro of F6R Locking system with central locking F6R Comfort Lock F6R Can light sensor G3Y Turbo retarder clutch G5G Mercedes Power Shift 3 H16 Driver's seat heating H16 Driver's seat heating H16 Ari suspension, rear axle J2H Multimedia radio touch J2K Speaker, 2-way system J2M Aux-in, a side wall shelf, right J3Z Axle load measuring device J3P Pre-installation for toll collection J3P Preparation for Truck Data Center 6 (DTCO) K3V AdBlue tank 60 liters K56 900-liter tank L1N Brown Installation H0	F4X Storage compartment outside flap left
F5L Sun visor, exterior, transparent F6R Air horns, cab roof F6E Locking system with central locking F6F Comfort Lock F6X Rain / light sensor G3Y Turbo retarder clutch G5G Mercedes PowerShift 3 H16 Driver's seat heating H4L Wheel formula 8x4/4 H6D Air suppension, rear axie J2H Multimedia radio touch J2K Speaker, 2-way system J2M Auchin, a side wall shelf, right J3Z Axie load measuring device J3D Pre-installation for toil collection J3D Preparation for Truck Data Center 6 (DTCO) K3V AdBlue tank 60 liters K56 900-liter tank L1A Bi-Xenon headlights L1P LED taillights L1P LED taillights L3Z Headlight washers M3V Motor OM473, R6, 15,61, 460 kW (625 hp) 3000 Nm M5M Tengine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N71 Motor output back, b, flange 100 mm, 650 Nm OYX Sight Package Q1Z Front spring 10.6 t, 3-lead Q4L Efifth wheel height, H= 190 mm R13 AUL Light metal irins S1H Lane keeping assistant S1L Alettness assistant	F4Y Storage compartment outer flap, right
F6R Locking system with central locking F6R Locking system with central locking F6R Condrot Lock F6X Rain / light sensor G3Y Turbo retarder clutch G5G Mercedes PowerShift 3 H16 Driver's seat heating H4L Wheel formula 8x4/4 H6X Air suspension, rear axle J2H Multimedia radio touch J2H Multimedia radio touch J2H Multimedia radio touch J3Z Speaker, 2-way system J3Z Axle load measuring device J3D Pre-installation for toil collection J3P) Pre-paralialition	F4Z f5b
F8E Corking system with central locking F8F comfort Lock F8X Rain / light sensor G3Y Turbo retarder clutch G5G Mercedes PowerShirt 3 H16 Driver's seat heating H4L Wheel formula 8x4/4 H6 Chi Ari suspension, rear axle J2H Multimedia radio touch J2K Speaker, 2-way system J2M Auxin, a side wall shelf, right J3Z Axie load measuring device J3D Pre-installation for toll collection J3PN Preparation for Truck Data Center 6 (DTCO) K3Y AdBlue tank 60 liters K56 900-liter tank L1A Bi-Xenon headlights L1A Bi-Xenon headlights L1A Bi-Xenon headlights L1A Bi-Ason headlights L3A Spotlight, below L3Z Headlight washers M3Y Motor OM473, R6, 15,61,460 kW (625 bp) 3000 Nm M5W Egine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake M5V Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm Q7X Sight Package Q1Z Front spring 10.5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1H Alctive Brake Assist 3 S5Z cruise control	F5L Sun visor, exterior, transparent
F8F comfort Lock F8X Rain / light sensor G3Y Turbo retarder clutch G3G Mercedes PowerShift 3 H16 Driver's seat heating H14 Wheel formula 8x4/4 H16 Driver's seat heating H14 Wheel formula 8x4/4 H15 Air suspension, rear axle J2H Multimedia radio touch J2K Spaaker, 2-way system J2K Aux-in, a side wall shelf, right J3Z Axle load measuring device J3D Pre-installation for foll collection J3N Preparation for Truck Data Center 6 (DTCO) K3N AdBlue tank 60 liters K56 900-liter tank L1A Bi-Xanon headlights L1N Fog lights, LED-Daytine running lights, cornering lights L1N Fog lights, LED-Daytine running lights, cornering lights L1A Bi-Alandilight washers L3A Spotlight, below L3Z Headlight washers L3A Headlight washers M3N Motor OM473, R6, 15,61, 460 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm Q7X Sight Package Q1Z Front spring 10.5 1, 3-leaf Q14, Firth wheel height, H = 190 mm R1.3 ALU light metal rims S1H Lane keeping assistant S1H Active Brake Assist 3 S5Z cruise control	F6R Air horns, cab roof
FBX Rain / light sensor G3Y Tutor retarder clutch G5G Mercedes PowerShift 3 H16 Driver's seat heating I4L Wheel formula 8x4/4 I6X Air suspension, rear axie J2H Multimedia radio touch J2K Speaker, 2-way system J2M Aux-in, a side wall shelf, right J3Z Akal load measuring device J3D Pre-installation for toll collection J3P Preparation for Truck Data Center 6 (DTCO) K3V AdBlue tank 60 liters K56 900-liter tank L1A Bi-Xenon headlights L1P LED taillights L1P LED taillights L3Z Abdlight washers M3W Motor OM473, R6, 15,61, 460 kW (625 kp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Tutocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10.51, 3-leaf Q1L Fifth, wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1M Active Brake Assist 3 S5Z cruise control	F8E Locking system with central locking
G3Y Turbo retarder clutch G5G Mercedes PowerShift 3 H16 Driver's seat heating HL Wheel formula 8x4/4 IEX Air suspension, rear axle J2H Multimedia radio touch J2K Speaker, 2-way system J2K Maxin, a side wall shelf, right J3Z Axle load measuring device J9D Pre-installation for toll collection J3P Preparation for Truck Data Center 6 (DTCO) K3V AdBlue tank 60 liters K56 900-liter tank L1A Bi-Xenon headlights L1N Fog lights, LED-Daytime running lights, cornering lights L1P LED taillight L3A Spottight, below L3Z Headlight washers M3V Motor OM473, R6, 15,6 I, 460 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package O4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1L Alertness assistant S1L Alertness assistant S1M Active Brake Assist 3 S5Z cruise control	F8F comfort Lock
GSG Mercedes PowerShift 3 H16 Driver's seat heating I4L Wheel formula 8x4/4 I4K Wheel Fark Wheel	F8X Rain / light sensor
H16 Driver's seat heating I4L Wheel formula 8x4/4 [6X Air suspension, rear axke J2H Multimedia radio touch J2K Speaker, 2-way system J2M Aux-in, a side wall shelf, right J3Z Axle load measuring device J3D Pre-installation for toll collection J3P Preparation for Truck Data Center 6 (DTCO) K3V AdBlue tank 60 liters K56 900-liter tank L1A Bi-Xenon headlights L1A Bi-Xenon headlights L1N Fog lights, LED-Daytime running lights, cornering lights L1A Bi-Xenon headlights L3A Spotlight, below L3Z Headlight washers M3V Motor OM473, R6, 15, 61, 460 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O'X Sight Package C1Z Front spring 10,5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1L Alerness assistant S1M Active Brake Assist 3 S5Z cruise control	G3Y Turbo retarder clutch
I4L Wheel formula 8x4/4 I6X Air suspension, rear axle J2H Multimedia radio touch J2K Speaker, 2-way system J2M Aux-in, a side wall shelf, right J3Z Axle load measuring device J3P Pre-installation for toll collection J3P Pre-paration for Truck Data Center 6 (DTCO) K3V AdBlue tank 60 liters K56 900-liter tank L1A Bi-Xenon headlights L1A Bi-Xenon headlights L1P LED taillights L3A Spotlight, below L3Z Headlight washers M3V Motor OutAr3, R6, 15,6,1,460 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O'TX Sight Package Q1Z Front spring 10,5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm R1.3 ALU light metal rims S1H Lane keeping assistant S1H Active Brake Assist 3 S5Z cruise control	G5G Mercedes PowerShift 3
I6X Air suspension, rear axle J2H Multimedia radio touch J2K Speaker, 2-way system J2M Aux-in, a side wall shelf, right J3Z Axle load measuring device J9D Pre-installation for toll collection J9N Preparation for Truck Data Center 6 (DTCO) K3V AdBlue tank 60 liters K56 900-liter tank L1N Boy lights, LED-Daytime running lights, cornering lights L1N Boy lights, LED-Daytime running lights, cornering lights L1N Epa lights, LED-Daytime running lights, cornering lights L1A Bi-Xenon headlights L3A Spotlight, below L3Z Headlight washers M3V Motor OM473, R6, 15,6 I, 460 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10.5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm R1.3 ALU light metal rims S1L Aletness assistant S1L Aletness assistant S1L Aletness assistant S1M Active Brake Assist 3	H16 Driver's seat heating
JZH Multimedia radio touch JZK Speaker, 2-way system JZM Aux-in, a side wall shelf, right J3Z Axle load measuring device J3PD Pre-installation for toll collection J9PD Pre-installation for Truck Data Center 6 (DTCO) K3V AdBlue tank 60 liters K56 900-liter tank L1A Bi-Xenon headlights L1N Fog lights, LED-Daytime running lights, cornering lights L1P LED taillights L3A Spotlight, below L3Z Headlight washers M3V Motor OM473, R6, 15,6 I, 460 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N3C Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10.5 I, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1L Alertness assistant S1L Alertness assistant S1L Alertness assistant S1M Active Brake Assist 3	I4L Wheel formula 8x4/4
JZK Speaker, 2-way system JZM Aux-in, a side wall shelf, right JZZ Alze load measuring device JPD Pre-installation for toll collection JPN Preparation for Truck Data Center 6 (DTCO) K3V AdBlue tank 60 liters K56 900-liter tank L1A Bi-Xenon headlights L1N Fog lights, LED-Daytime running lights, cornering lights L1P LED taillights L1P LED taillights L3Z Headlight washers M3V Motor OM473, R6, 15,6 I, 460 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake M6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10.5 I, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1L Alertness assistant S1L Alertness assistant S1L Alertness assistant S1M Active Brake Assist 3	I6X Air suspension, rear axle
JZM Aux-in, a side wall shelf, right JZZ Axle load measuring device JBD Pre-installation for toll collection JBN Preparation for Truck Data Center 6 (DTCO) K3V AdBlue tank 60 liters K56 900-liter tank L1A Bi-Xenon headlights L1N Fog lights, LED-Daytime running lights, cornering lights L1P LED taillights L3A Spotlight, below L3Z Headlight washers M3V Motor OM473, R6, 15,6 I, 460 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10.5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1M Active Brake Assist 3	J2H Multimedia radio touch
J3Z Axle load measuring device J9D Pre-installation for toll collection J9N Preparation for Truck Data Center 6 (DTCO) K3V AdBlue tank 60 liters K56 900-liter tank L1A Bi-Xenon headlights L1N Fog lights, LED-Daytime running lights, cornering lights L1P LED taillights L3A Spotlight, below L3Z Headlight washers M3V Motor OM473, R6, 15,6 I, 460 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10,5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm R13 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1L Alertness assistant S1L Alertness assistant S1M Active Brake Assist 3	J2K Speaker, 2-way system
J9D Pre-installation for full collection J9N Preparation for Truck Data Center 6 (DTCO) K3V AdBlue tank 60 liters K56 900-liter tank L1A Bi-Xenon headlights L1N Fog lights, LED-Daytime running lights, cornering lights L1P LED taillights L3A Spotlight, below L3A Headlight washers M3V Motor OM473, R6, 15,6 I, 460 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N62 Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10.5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1L Alertness assistant S1M Active Brake Assist 3	J2M Aux-in, a side wall shelf, right
J9N Preparation for Truck Data Center 6 (DTCO) K3V AdBlue tank 60 liters K56 900-liter tank L1A Bi-Xenon headlights L1N Fog lights, LED-Daytime running lights, cornering lights L1P LED taillights L3A Spotlight, below L3Z Headlight washers M3V Motor OM473, R6, 15,6 l, 460 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10.5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1L Alertness assistant S1M Active Brake Assist 3 S5Z cruise control	J3Z Axle load measuring device
K3V AdBlue tank 60 liters K56 900-liter tank L1A Bi-Xenon headlights L1N Fog lights, LED-Daytime running lights, cornering lights L1P LED taillights L3A Spotlight, below L3Z Headlight washers M3V Motor OM473, R6, 15,6 I, 460 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10.5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1L Alertness assistant S5Z cruise control	J9D Pre-installation for toll collection
K56 900-liter tank L1A Bi-Xenon headlights L1N Fog lights, LED-Daytime running lights, cornering lights L1P LED taillights L3A Spotlight, below L3Z Headlight washers M3V Motor OM473, R6, 15,6 I, 460 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10.5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1L Alertness assistant S1M Active Brake Assist 3 S5Z cruise control	J9N Preparation for Truck Data Center 6 (DTCO)
L1A Bi-Xenon headlights L1N Fog lights, LED-Daytime running lights, cornering lights L1P LED taillights L3A Spotlight, below L3Z Headlight washers M3V Motor OM473, R6, 15,6 I, 460 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10.5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1L Alertness assistant S5Z cruise control	K3V AdBlue tank 60 liters
L1N Fog lights, LED-Daytime running lights, cornering lights L1P LED taillights L3A Spotlight, below L3Z Headlight washers M3V Motor OM473, R6, 15,6 I, 460 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10.5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1L Alertness assistant S1M Active Brake Assist 3 S5Z cruise control	K56 900-liter tank
L1P LED taillights L3A Spotlight, below L3Z Headlight washers M3V Motor OM473, R6, 15,6 I, 460 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10.5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1L Alertness assistant S1M Active Brake Assist 3 S5Z cruise control	
L3A Spotlight, below L3Z Headlight washers M3V Motor OM473, R6, 15,6 I, 460 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10.5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1M Active Brake Assist 3 S5Z cruise control	L1N Fog lights, LED-Daytime running lights, cornering lights
L3Z Headlight washers M3V Motor OM473, R6, 15,6 I, 460 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10.5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1L Alertness assistant S1M Active Brake Assist 3 S5Z cruise control	
M3V Motor OM473, R6, 15,6 I, 460 kW (625 hp) 3000 Nm M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10.5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1M Active Brake Assist 3 S5Z cruise control	L3A Spotlight, below
M5M Engine version Euro 6, with OBD-C M5T Turbocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10.5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1L Alertness assistant S1M Active Brake Assist 3 S5Z cruise control	
M5T Turbocompound M5V High Performance Engine Brake N6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10.5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1L Alertness assistant S1M Active Brake Assist 3 S5Z cruise control	
M5V High Performance Engine Brake N6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10.5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1M Active Brake Assist 3 S5Z cruise control	
N6Z Transmission oil cooling N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10.5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1M Active Brake Assist 3 S5Z cruise control	
N7I Motor output back, b, flange 100 mm, 650 Nm O7X Sight Package Q1Z Front spring 10.5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1M Active Brake Assist 3 S5Z cruise control	
O7X Sight Package Q1Z Front spring 10.5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1M Active Brake Assist 3 S5Z cruise control	·
Q1Z Front spring 10.5 t, 3-leaf Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1M Active Brake Assist 3 S5Z cruise control	
Q4L Fifth wheel height, H = 190 mm RL3 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1M Active Brake Assist 3 S5Z cruise control	
RL3 ALU light metal rims S1H Lane keeping assistant S1L Alertness assistant S1M Active Brake Assist 3 S5Z cruise control	
S1H Lane keeping assistant S1L Alertness assistant S1M Active Brake Assist 3 S5Z cruise control	
S1L Alertness assistant S1M Active Brake Assist 3 S5Z cruise control	
S1M Active Brake Assist 3 S5Z cruise control	
S5Z cruise control	
UTW Audiue pipes, water-fleateu	
	OTW Aublue pipes, water-neateu

V6P Heavy duty tractor unit

X67 Step and platform behind cab

Y1X Refrigerator, in drawers, under the bed

Y21 Storage box

Z1H EBS

Z3Y Metallic-Lack

Z99 Vehicle without sparewheel

Legal notice: The details of this offer are subject to change.

 Subject to prior sale. For sale to businesses only.

© 2005 **AVG** Trucks GmbH